

**Product information on solid fuel local space heaters
according to Comission regulation (EU) 2015/1185**



Model	HWAM 4110, HWAM 4120, HWAM 4130, HWAM 4140, HWAM 4150, HWAM 4160, HWAM 4240
Direct heat output [kW]	4,7
Indirect heating functionality	No
Indirect heat output [kW]	-
Type of heat output/room temperature control	Two ore more manual stages, no temperature control

Space heating performance at nominal heat output		
Fuel	Preferred fuel	Seasonal space heating energy efficiency [%]
Wood logs with moisture content 12-18 %	Yes	72
Emissions	mg/m³ (13% O₂)	
Particulate matter (PM)	24	
Organic gaseous compounds (OGC)	65	
Carbon monoxide (CO)	1125	
Nitrogen dioxid (NO ₂)	92	

Characteristics when operating with the preferred fuel only		
Nominal heat output [kW]		4,7
Electric power consumption nominal heat output [kW]		-
Electric power consumption minimum heat output [kW]		-
Electric power consumption standby mode [kW]		-
Useful efficiency at nominal heat output [%]		82
Energy efficiency index		109
Energy efficiency class		A+

Specific Precautions during Assembling, Installing & Maintenance:

See installation instructions for more information

Product End-of-Life/Recycling:

To dispose of the stove after the product life has expired, please observe the following information

- Dispose of the items correctly i.e. separate the parts to be disposed of in material groups
- Always dispose of items in a way that is as sustainable as possible and that is in line with the current environmental protection, reprocessing/recycling and disposal technology