HWAM intelligent heat

HWAM 5420
HWAM 5440
HWAM 5460

AUTOPILOT™

UK Declaration of Performance. 2

Declaration of Performance

UK

Construction Products Regulation (CPR) 2011 (retained EU law EUR 305/2011) as ammended.
Nr. 0159 - 01/04/2025

No.: 542W-AUT-02-V01 Date: 20-04-2026

EN 16510-1:2022, Annex A

NO.	Information according to (EU) 305/2011	Registration by the manufacturer
1	Unique identification code of the product type	HWAM 5420 wall mount
2	Intended use(s)	Space heating in residential buildings
3	Manufacturer / trade mark	**HWAM A/S** Nydamsvej 53 8362 Hørning Denmark www.hwam.com
4	Authorised representative	Not relevant
5	System(s) of assessment and verification of consistency of performance of the construction product	System 3
6	The notified test laboratory has performed the initial test according to system 3. Notified body(ies) Test report no.	Teknologisk institut Kongsvang 29 DK-8000 Aarhus NB 1235 300-ELAB-2782-EN
7	Harmonised technical specifications	EN 16510-2-1:2022
8	**Essential characteristics**	
	Mechanical resistance and stability	
	Load bearing capacity	122 kg
	Safety in case of fire	
	Protection of combustible materials Minimum disance to combustible materials - insulated flue gas pipe.	**Protection of combustible materials** Minimum disance to combustible materials - uninsulated flue gas pipe.
	Bottom (dB) 300 mm	Bottom (dB) 300 mm
	Floor in front (dF) 0 mm	Floor in front (dF) 0 mm
	Ceiling (dC) 700 mm	Ceiling (dC) 650 mm
	Rear (dR) 75 mm	Rear (dR) 150 mm
	Side (dSs) 150 mm	Side (dSs) 150 mm
	Side radiation area (dS) 450 mm	Side radiation area (dS) 450 mm
	Corner, 45° (dSc) 100 mm	Corner, 45° (dSc) 75 mm
	Mantel piece 700 mm	Mantel piece 650 mm
	Distance to eg. furnuture (dP) 1350 mm	Distance to eg. Furnuture (dP) 1350 mm
	Hygiene, health and environment	
	Emissions at nominal heat output	Carbon monoxide emission (CO) 879 mg/m^3
		Nitrogen emission (NOx) 85 mg/m^3
		Emission of organic gaseous carbon (OGC) 83 mg/m^3
		Particulate matter emissions (PM) 29 mg/m^3
	Safety and accessibility in use	
	Data for installation to a chimney at nominal heat output	Flue gas outlet temperature 367 °C
		Minimum flue draught 12 Pa
		Flue gas mass flow 5,2 g/s
	Data for installation on a chimney with regarding fire safety on safety test heat output	Fire safety for installation to the chimney T400 G

8	**Energy economy and heat retention**			
	Appliance's thermal output and energy efficiency at nominal heat output	Space heat output	6,6	kW
		Efficiency	80	%
	Space heating efficiency	Seasonal space heating efficiency at nominal heat output	70	%
		Energy Efficiency		
		Energy Efficiency Index (EEI)	106	
		Energy efficiency class	A	
		Electric power consumption at appliance's nominal heat output	NDP	kW
		Power consumption in standby mode	NDP	kW
	Sustainable use of natural resources			
	Environmental sustainability		NPD	
9	The performance of the above product corresponds to the declared performance according to number 8. This declaration of performance is issued under the sole responsibility of the manufacturer in accordance with point 3.			

Hørning
20-04-2026

Jens Gert Christensen, CTO



Declaration of Performance

UK

Construction Products Regulation (CPR) 2011 (retained EU law EUR 305/2011) as ammended.
Nr. 0159 - 01/04/2025

No.: 542L-AUT-02-V01 Date: 20-04-2026

EN 16510-1:2022, Annex A

NO.	Information according to (EU) 305/2011	Registration by the manufacturer
1	Unique identification code of the product type	HWAM 5420 plinth
2	Intended use(s)	Space heating in residential buildings
3	Manufacturer / trade mark	**HWAM A/S** Nydamsvej 53 8362 Hørning Denmark www.hwam.com
4	Authorised representative	Not relevant
5	System(s) of assessment and verification of consistency of performance of the construction product	System 3
6	The notified test laboratory has performed the initial test according to system 3. Notified body(ies) Test report no.	Teknologisk institut Kongsvang 29 DK-8000 Aarhus NB 1235 300-ELAB-2782-EN
7	Harmonised technical specifications	EN 16510-2-1:2022
8	**Essential characteristics**	
	Mechanical resistance and stability	
	Load bearing capacity	122 kg
	Safety in case of fire	
	Protection of combustible materials Minimum disance to combustible materials - insulated flue gas pipe.	**Protection of combustible materials** Minimum disance to combustible materials - uninsulated flue gas pipe.
	Bottom (dB) 0 mm	Bottom (dB) 0 mm
	Floor in front (dF) 550 mm	Floor in front (dF) 550 mm
	Ceiling (dC) 700 mm	Ceiling (dC) 650 mm
	Rear (dR) 75 mm	Rear (dR) 150 mm
	Side (dSs) 150 mm	Side (dSs) 150 mm
	Side radiation area (dS) 450 mm	Side radiation area (dS) 450 mm
	Corner, 45° (dSc) 100 mm	Corner, 45° (dSc) 75 mm
	Mantel piece 700 mm	Mantel piece 650 mm
	Distance to eg. furnuture (dP) 1350 mm	Distance to eg. Furnuture (dP) 1350 mm
	Hygiene, health and environment	
	Emissions at nominal heat output	Carbon monoxide emission (CO) 879 mg/m^3
		Nitrogen emission (NOx) 85 mg/m^3
		Emission of organic gaseous carbon (OGC) 83 mg/m^3
		Particulate matter emissions (PM) 29 mg/m^3
	Safety and accessibility in use	
	Data for installation to a chimney at nominal heat output	Flue gas outlet temperature 367 °C
		Minimum flue draught 12 Pa
		Flue gas mass flow 5,2 g/s
	Data for installation on a chimney with regarding fire safety on safety test heat output	Fire safety for installation to the chimney T400 G

8	**Energy economy and heat retention**			
	Appliance's thermal output and energy efficiency at nominal heat output	Space heat output	6,6	kW
		Efficiency	80	%
	Space heating efficiency	Seasonal space heating efficiency at nominal heat output	70	%
		Energy Efficiency		
		Energy Efficiency Index (EEI)	106	
		Energy efficiency class	A	
		Electric power consumption at appliance's nominal heat output	NDP	kW
		Power consumption in standby mode	NDP	kW
	Sustainable use of natural resources			
	Environmental sustainability		NPD	
9	The performance of the above product corresponds to the declared performance according to number 8. This declaration of performance is issued under the sole responsibility of the manufacturer in accordance with point 3.			

Hørning
20-04-2026

Jens Gert Christensen, CTO



Declaration of Performance

UK

Construction Products Regulation (CPR) 2011 (retained EU law EUR 305/2011) as ammended.
Nr. 0159 - 01/04/2025

No.: 5446S-AUT-02-V01 Date: 20-04-2026

EN 16510-1:2022, Annex A

NO.	Information according to (EU) 305/2011			Registration by the manufacturer		
1	Unique identification code of the product type			HWAM 5440, HWAM 5440 stone, HWAM 5460, HWAM 5460 stone		
2	Intended use(s)			Space heating in residential buildings		
3	Manufacturer / trade mark			**HWAM A/S** Nydamsvej 53 8362 Hørning Denmark www.hwam.com		
4	Authorised representative			Not relevant		
5	System(s) of assessment and verification of consistency of performance of the construction product			System 3		
6	The notified test laboratory has performed the initial test according to system 3. Notified body(ies) Test report no.			Teknologisk institut Kongsvang 29 DK-8000 Aarhus NB 1235 300-ELAB-2782-EN		
7	Harmonised technical specifications			EN 16510-2-1:2022		
8	**Essential characteristics**					
	Mechanical resistance and stability					
	Load bearing capacity				122	kg
	Safety in case of fire					
	Protection of combustible materials Minimum disance to combustible materials - insulated flue gas pipe.			**Protection of combustible materials** Minimum disance to combustible materials - uninsulated flue gas pipe.		
	Bottom (dB)	0	mm	Bottom (dB)	0	mm
	Floor in front (dF)	0	mm	Floor in front (dF)	0	mm
	Ceiling (dC)	700	mm	Ceiling (dC)	650	mm
	Rear (dR)	75	mm	Rear (dR)	150	mm
	Side (dSs)	150	mm	Side (dSs)	150	mm
	Side radiation area (dS)	450	mm	Side radiation area (dS)	450	mm
	Corner, 45° (dSc)	100	mm	Corner, 45° (dSc)	75	mm
	Mantel piece	700	mm	Mantel piece	650	mm
	Distance to eg. furnuture (dP)	1350	mm	Distance to eg. Furnuture (dP)	1350	mm
	Hygiene, health and environment					
	Emissions at nominal heat output			Carbon monoxide emission (CO)	879	mg/m^3
				Nitrogen emission (NOx)	85	mg/m^3
				Emission of organic gaseous carbon (OGC)	83	mg/m^3
				Particulate matter emissions (PM)	29	mg/m^3
	Safety and accessibility in use					
	Data for installation to a chimney at nominal heat output			Flue gas outlet temperature	367	°C
				Minimum flue draught	12	Pa
				Flue gas mass flow	5,2	g/s
	Data for installation on a chimney with regarding fire safety on safety test heat output			Fire safety for installation to the chimney	T400 G	

8	**Energy economy and heat retention**			
	Appliance's thermal output and energy efficiency at nominal heat output	Space heat output	6,6	kW
		Efficiency	80	%
	Space heating efficiency	Seasonal space heating efficiency at nominal heat output	70	%
		Energy Efficiency		
		Energy Efficiency Index (EEI)	106	
		Energy efficiency class	A	
		Electric power consumption at appliance's nominal heat output	NDP	kW
		Power consumption in standby mode	NDP	kW
	Sustainable use of natural resources			
	Environmental sustainability		NPD	
9	The performance of the above product corresponds to the declared performance according to number 8. This declaration of performance is issued under the sole responsibility of the manufacturer in accordance with point 3.			

Hørning
20-04-2026

Jens Gert Christensen, CTO

www.hwam.com